



Acer Projector S1286H - XGA, 3500 Lumens

Model No: ACER-PJ-S1286H



Price:

Rs. 239,499

Warranty:

3 Years(s) manufacturer warranty.

3 Years (Lamp: 1 Year Or 1,000 Hours Whichever Comes First).

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- Model: Acer Projector S1286H
- Type: Projector
- Brightness: 3,500 ANSI Lumens (Standard), 2,800 ANSI Lumens (ECO)
- Native Resolution: XGA (1,024 x 768)
- Aspect Ratio: 4:3 (Native), 16:9 (Supported)
- Contrast Ratio: 20,000:1
- Zoom Ratio: 1X Optical 2x Digital
- Throw Ratio: 0.617 (77" @97cm)
- Projection Lens: 3F = 2.70, f = 7.15mm, Manual Focus
- Projection Screen Size: 32"~ 300"(82cm~762cm)
- Projection Distance: 0.4m~ 3.8m (1.3'~12.3')
- Projection Offset (By Half Height): 1.15
- Keystone Correction: (Vertical, Manual)+/-40°
- Audio: 16W Speaker x 1
- Lamp Type: Osram 220W
- Lamp Life: 4,000 Hours (Standard), 6,000 Hours (ECO), 10,000 Hours (ExtremeEco)
- Noise Level: 32 dBA (Standard), 24 dBA (ECO)
- Input Interface: Analog RGB/Component Video (D-sub) HDMI (Video, Audio, HDCP) / PC Audio (Stereo mini jack) / Composite Video (RCA)
- Output Interface: PC Audio (Stereo mini jack) x 1, DC Out (5V/1A, USB Type A) x 1, Analog RGB (D-sub) x 1
- Control Interface: RS232 (D-sub) x 1
- Projection System: DLP
- Display Panel: 0.55" DarkChip™ 3 DMD
- Computer Compatibility: IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards, WUXGA (1,920 x 1,200), 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600) / VGA (640 x 480)

- Video Compatibility: NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
- Displayable Colors: 1.07 Billion Colors
- Horizontal Scan Rate: 15k ~ 100k Hz
- Vertical Refresh Scan Rate: 24 ~ 120 Hz
- Projection Mode: Front, Rear, Front-Ceiling, Rear-Ceiling
- Uniformity: 0.85
- Ceiling Mounting: Yes
- Remote Control: IR remote control, Laser pointer, PgUp/PgDn functions
- Power Supply: AC input 100~240V, 50/60 Hz
- Power Consumption: 270 Watts (Standard), 210 Watts (ECO), <0.5 Watts (Standby)
- Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F)
- Operating Humidity: 80%RH (Max.)
- Standard Accessories: AC power cord, VGA cable, Remote control, Battery for remote control, Lens cap, Carrying case, User's guide (CD-ROM) Quick start guide
- Weight: 3.1 Kg (6.8 lbs)
- Dimensions: 313 mm X 255.25 mm X 113.7 mm (w/ feet) (12.3" x 10" x 4.5")

Date: 2026-06-17 23:37