



HP Ink Tank 115 Printer

Model No: HP-INKTANK-115



Price:

Rs. 49,999

Warranty:

1 Year(s) manufacturer warranty.
1 Year Manufacturer Warranty.

Delivery:

Delivery - Standard 3 To 5 Working Days.

- Delivery Within 3 Working Days For Colombo And Suburbs, 5 Working Days For Other Locations.
- For Any Invoice Up To Rs.9,999, A Delivery Rate Of Rs.500 Will Be Charged.
- For Any Invoice From Rs.10,000 To 19,999, A Delivery Rate Of Rs.700 Will Be Charged.
- For Any Invoice From Rs.20,000 To 49,999, A Delivery Rate Of Rs.900 Will Be Charged.
- For Any Invoice From Rs.50,000 To 99,999, A Delivery Rate Of Rs.1200 Will Be Charged.
- For Any Invoice From Rs.100,000 To 149,999, A Delivery Rate Of Rs.1500 Will Be Charged.
- For Any Invoice From Rs.150,000 And Above, A Delivery Rate Of Rs.2000 Will Be Charged.

Specifications:

- Type: Inject - Single Function
- Model: INK TANK 115
- Printing Resolution: Black (best): Up to 1200 x 1200 rendered dpi; Colour (best): Up to 4800 x 1200 optimised dpi colour (when printing from a computer and 1200 input dpi)
- Print Head / Ink - Ink Bottles / Toner Cartridge: Ink Bottles
- Print Speed: Black: Up to 19 ppm (draft, A4); Up to 8 ppm (ISO); Colour: Up to 16 ppm (draft, A4); Up to 5 ppm (IS)
- Printable Width - Bordered: Yes, up to 210 x 297 mm (A4)
- Printable Width - Borderless: Borderless printing up to 210 x 297 mm (A4)
- Printable Area - Borderless Printing: A4; B5; A6; DL envelope
- Paper Size: A4; B5; A6; DL envelope (Note: Many other sizes are also supported. Any size between 3 x 5" and 8.5 x 14")
- Paper Handling (Rear Tray): A4; B5; A6; DL envelope
- Paper Handling (Front Tray): 60-sheet input tray; 25-sheet output tray
- Paper Weight: A4: 60 to 90 g/m²; HP envelopes: 75 to 90 g/m²; HP cards: up to 200 g/m²; HP 10 x 15 cm photo paper: up to 300 g/m²
- Ink End Sensor: Page Count
- Print Head Alignment: Manual
- Bluetooth / NFC / Wifi: NO
- Network - Network Protocol: USB
- Network - Wireless LAN: Wired
- System Requirements: Microsoft® Windows® 10, 8.1, 8, Windows Vista®, Windows® XP SP3 or higher (32-bit only): Windows Server 2008 32-bit (SP1 or greater), Windows Server 2008 64-bit (SP1 or greater), Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016, OS X v10.10 Yosemite, OS X v10.11 El Capitan, macOS Sierra v10.12 (previously OS X), Linux O
- Operation Panel: 7 segment + icon LCD
- Device Memory: Integrated
- Interface: 1 Hi-Speed USB 2.0

- Paper Output Tray: 60-sheet input tray; 25-sheet output tray
- Operating Environment: Operating temperature range: 5 to 40° C; Recommended operating temperature range: 15 to 30° C; Operating humidity range: 15 to 80% RH (non-condensing); Recommended operating humidity range: 20 to 80% RH;
- Storage Environment: Storage temperature range: -40 to 60° C; Energy Savings Feature Technology: HP Auto-Off Technology
- Power Consumption: 10 watts maximum, 0.07 watts (Off), 2.1 watts (Standby), 0.88 watt (Sleep)
- Duty Cycle: Up to 1,000 pages
- Number Of Pages (Yield): 8,000 pages colour or 6,000 pages black
- Dimension (W x D x H): 523 x 284 x 138.5 mm
- Weight: 3.4 kg
- Colors: Black

Date: 2026-06-13 20:27